

## MATERIAL SAFETY DATA SHEET

FABRITEC INTERNATIONAL  
 1157 INDUSTRIAL ROAD  
 COLD SPRING, KY 41076  
 EMERGENCY CONTACT: HAROLD E. MAINS (859) 781-8200  
 CHEMTREC ASSISTANCE: (800) 262-8200 (U.S.A. & CANADA)

MSDS NO.: 6750  
 DATE: FEB. 2008  
 PAGE: 1 OF 2

## 1. PRODUCT NAME &amp; HAZARD SUMMARY

**6750 PRETREAT GES** PRE-SPOTTER & LEVELING AGENT FOR GREEN EARTH<sup>SM</sup> SOLUTION  
 PRIMARY USE: PRESPOTTER AND LEVELING AGENT FOR GREEN EARTH<sup>SM</sup> SOLUTION

NFPA HAZARD	RATING	SARA TITLE III, SECTION 313	CANADA (WHMIS)
HEALTH	2 MODERATE	APPLICABLE ( )	B: FLAMMABLE, COMBUSTIBLE
FIRE	1 SLIGHT	NOT APPLICABLE (X)	
REACTIVITY	0 MINIMAL		

2. HAZARDOUS COMPONENTS	%	OSHA (PPM)	ACGIH (PPM)	LD 50 (MG/KG)
-------------------------	---	------------	-------------	---------------

INGREDIENTS NOT IDENTIFIED ARE NON-HAZARDOUS.

## 3. PHYSICAL &amp; CHEMICAL DATA

APPEARANCE: LIQUID	EVAPORATION RATE (ETHER = 1): LESS THAN WATER
ODOR: MILD	VAPOR DENSITY (AIR = 1): N.AV.
BOILING PT.: >360°F (182°C)	VAPOR PRESSURE (MM): N.AV.
FREEZING PT.: 20°F (-6°C)	SOLUBILITY IN WATER: NEGLIGIBLE
pH: N.AP.	SPECIFIC GRAVITY (WATER = 1): 0.95
% VOLATILE: 20%	CO-EFFICIENT OF WATER/OIL DISTRIBUTION: N.AV.
ODOR THRESHOLD (PPM): N.AV.	

## 4. FIRE &amp; EXPLOSION HAZARDS

FLASH POINT:  $\geq 170^{\circ}\text{F}$  ( $76^{\circ}\text{C}$ )  
 FLAMMABLE LIMITS IN AIR, % BY VOLUME: Not Determined  
 FIRE FIGHTING MEDIA (1990 EMERGENCY RESPONSE GUIDEBOOK, DOT P 5800.5): Dry chemical, CO<sub>2</sub>, water spray or foam spray  
 SPECIAL FIRE-FIGHTING PROCEDURES: Wear self-contained breathing apparatus  
 UNUSUAL FIRE AND EXPLOSION HAZARDS: None  
 HAZARDOUS COMBUSTION PRODUCTS: Oxides of Carbon  
 CONDITIONS OF FLAMMABILITY: High heat and sources of ignition  
 AUTO IGNITION TEMP. ( $^{\circ}\text{C}$ ): N.AV.  
 EXPLOSION DATA: - SENSITIVITY TO MECHANICAL IMPACT: N.AV.  
 SENSITIVITY TO STATIC DISCHARGE: N.AV.

## 5. REACTIVITY HAZARD DATA

STABILITY (CONDITIONS TO AVOID): Stable  
 INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidizing agents  
 HAZARDOUS DECOMPOSITION PRODUCTS: Thermal decomposition may release Oxides of Carbon  
 HAZARDOUS POLYMERIZATION (CONDITIONS TO AVOID): Will not occur

## 6. HEALTH HAZARD DATA

PRIMARY ROUTES OF ENTRY:            INHALATION\_\_\_\_            SKIN\_X\_            INGESTION\_\_\_\_

WARNING! MAY CAUSE EYE, SKIN AND RESPIRATORY IRRITATION. MAY BE HARMFUL IF SWALLOWED.

SIGNS & SYMPTOMS OF EXPOSURE: (ACUTE & CHRONIC)

EYES: Liquid and vapors may cause irritation.

SKIN: Prolonged contact may cause defatting of skin, which can lead to irritation, dermatitis, folliculitis, oil acne, melanosis, and rarely warts.

INGESTION: May cause gastrointestinal disturbances such as nausea, vomiting and diarrhea. Aspiration into lungs from vomiting will cause lung damage, which could be fatal.

## 6. HEALTH HAZARD DATA (cont'd)

INHALATION: Low hazard unless heated or misted. May cause irritation of throat and nose, dizziness and lung edema with chest tightness.

IRRITANCY OF PRODUCT: N.AV.

SENSITIZATION TO PRODUCT: N.AV.

CARCINOGENICITY, REPRODUCTIVE TOXICITY, TERATOGENICITY, MUTAGENICITY: N.AV.

TOXICOLOGICALLY SYNERGISTIC PRODUCTS: N.AV.

EMERGENCY AND FIRST AID PROCEDURES:

EYES: Remove contact lenses, if worn. Flush with water for at least 15 min. Call a physician.

SKIN: Flush with water. Remove contaminated clothing.

INHALATION: Remove to fresh air. If breathing has stopped, give artificial respiration. If breathing is difficult, give oxygen, if available. Get medical help.

INGESTION: If conscious, give large amounts of water. Do NOT induce vomiting, get medical help. If vomiting occurs, keep head below hips to prevent aspiration into lungs.

## 7. SPILL AND LEAK PROCEDURES

Remove sources of ignition.

LARGE SPILLS: Contain and transfer to drums for use or disposal.

SMALL SPILLS: Absorb onto rags. Clean rags in cleaning unit.

WASTE DISPOSAL METHOD: Dispose of according to all applicable regulations. Incineration in permitted facilities or disposal in permitted land fill are preferred disposal methods.

HANDLING PROCEDURES & EQUIPMENT: Avoid direct contact.

STORAGE REQUIREMENTS: Keep away from heat and sources of ignition.

## 8. SPECIAL PROTECTION, PREVENTATIVE MEASURES/IN CASE OF LARGE SPILL OR FIRE

ENGINEERING CONTROLS/VENTILATION: Local exhaust system sufficient to maintain exposure level below TWA values

RESPIRATOR: THE FOLLOWING RESPIRATORS ARE RECOMMENDED & RANKED IN ORDER FROM MIN. TO MAX. PROTECTION:

CHEMICAL CARTRIDGE RESPIRATOR WITH AN ORGANIC VAPOR CARTRIDGE WITH A FULL FACE PIECE.

GAS MASK WITH ORGANIC VAPOR CANISTER WITH A FULL FACE PIECE.

TYPE 'C' SUPPLIED-AIR RESPIRATOR WITH FULL FACE PIECE.

SELF-CONTAINED BREATHING APPARATUS WITH A FULL FACE PIECE OPERATED IN PRESSURE-DEMAND.

PERSONAL PROTECTIVE EQUIPMENT: Wear goggles when handling product, petroleum solvent resistant gloves.

## 9. TRANSPORTATION DATA

DOT HAZARD CLASSIFICATION 49 CFR 172.101: None, not regulated

DOT LABEL: None

UN, IATA: Not regulated

## 10. STATE RIGHT TO KNOW INFORMATION

SILICONE FLUID C.A.S. #541-02-6, DIPROPYLENE GLYCOL MONOMETHYLETHER C.A.S. #34590-94-8, DIPROPYLENE GLYCOL MONOMETHYLETHER ACETATE C.A.S. #88917-22-0, SODIUM DIOCTYL SULFOSUCCINATE C.A.S. #577-11-7, PROPYLENE GLYCOL C.A.S. #57-55-6

## ABBREVIATIONS:

OSHA = Occupational Safety & Health Administration

TWA = Time Weighted Average for 8 Hours

Mg/M<sup>3</sup> = Milligrams per Cubic Meter of Air

NFPA = National Fire Protection Agency

(C) = Ceiling, Limit for Exposure

DOT = Department of Transportation

MG/KG = Milligrams per Kilogram (1,000 grams)

WHMIS = Workplace Hazardous Materials Information System - Canada

ACGIH = American Conference of Government Industrial Hygienists

R.Q. = Amount of spill that must be reported to EPA

SARA Title III, Sec. 313 = Superfund Amendments and Reauthorization Act

C.A.S. = Chemical Abstract Service Number

LD 50 = Lethal Dose for 50% Test Animals

PEL = Permissible Exposure Level

STEL = Short Term Exposure Level (15 min)

ppm = part(s) per million

SKN = Skin Effects

IATA = International Air Transport Association

N.AV. = Not Available

N.AP. = Not Applicable

U.N. = United Nations

WE CANNOT ANTICIPATE ALL CONDITIONS UNDER WHICH THIS INFORMATION AND OUR PRODUCTS, OR THE PRODUCTS OF OTHER MANUFACTURERS IN COMBINATION WITH OUR PRODUCTS, MAY BE USED. WE ACCEPT NO RESPONSIBILITY FOR RESULTS OBTAINED BY THE APPLICATION OF THIS INFORMATION OR THE SAFETY AND SUITABILITY OF OUR PRODUCTS, EITHER ALONE OR IN COMBINATION WITH OTHER PRODUCTS. WE SELL THE PRODUCTS WITHOUT WARRANTY, AND BUYERS AND USERS ASSUME ALL RESPONSIBILITY AND LIABILITY FOR LOSS OR DAMAGE ARISING FROM THE HANDLING AND USE OF OUR PRODUCTS, WHETHER ALONE OR IN COMBINATION WITH OTHER PRODUCTS.