

FABRITEC INTERNATIONAL
 1157 INDUSTRIAL ROAD
 COLD SPRING, KY 41076
 EMERGENCY CONTACT: HAROLD E. MAINS (859) 781-8200
 CHEMTREC ASSISTANCE: (800) 262-8200 (U.S.A. & CANADA)

MSDS NO.: 6770
 DATE: FEB. 2008
 PAGE: 1 OF 2

 1. PRODUCT NAME & HAZARD SUMMARY

STAMFORD 6770 ODEX PLUS SMOKE & ODOR NEUTRALIZER

PRIMARY USE: ODOR NEUTRALIZER

NFPA HAZARD	RATING	SARA TITLE III, SECTION 313	CANADA (WHMIS)
HEALTH	0 MINIMAL	APPLICABLE ()	D2: CAUSING OTHER TOXIC EFFECTS
FIRE	0 MINIMAL	NOT APPLICABLE (X)	B; FLAMMABLE, COMBUSTIBLE
REACTIVITY	0 MINIMAL		

 2. HAZARDOUS COMPONENTS

	%	OSHA (PPM)	ACGIH (PPM)	LD 50 (MG/KG)
ISOPROPYL ALCOHOL	≤ 9.0	PEL N.A.V.	TWA STEL N.A.V. 25(C)	3,700 ORAL-RAT
C.A.S. #67-63-0				

INGREDIENTS NOT IDENTIFIED ARE NON-HAZARDOUS.

 3. PHYSICAL & CHEMICAL DATA

APPEARANCE: YELLOW COLORED LIQUID	EVAPORATION RATE: EQUAL TO WATER
ODOR: MILD	VAPOR DENSITY (AIR =1): N.AP.
BOILING PT.: 212°F (100°C)	VAPOR PRESSURE (MM): N.AP.
FREEZING PT.: APPROX. 320°F (°C)	SOLUBILITY IN WATER: SOLUBLE
pH: APPROX. 7.0	SPECIFIC GRAVITY (WATER = 1): 1.02
% VOLATILE: 80%	CO-EFFICIENT OF WATER/OIL DISTRIBUTION: N.A.V.
ODOR THRESHOLD (PPM): N.A.V.	

 4. FIRE & EXPLOSION HAZARDS

FLASH POINT: None
 FLAMMABLE LIMITS IN AIR, % BY VOLUME: N.AP.
 FIRE FIGHTING MEDIA (1990 EMERGENCY RESPONSE GUIDEBOOK, DOT P 5800.5): Dry chemical, CO₂, water spray or alcohol foam.
 SPECIAL FIRE-FIGHTING PROCEDURES: Wear self-contained breathing apparatus.
 UNUSUAL FIRE AND EXPLOSION: None
 HAZARDOUS COMBUSTION PRODUCTS: Oxides of Carbon
 CONDITIONS OF FLAMMABILITY: Not flammable
 AUTO IGNITION TEMP. (°C): N.AP.
 EXPLOSION DATA: - SENSITIVITY TO MECHANICAL IMPACT: N.AP.
 SENSITIVITY TO STATIC DISCHARGE: N.AP.

 5. REACTIVITY HAZARD DATA

STABILITY (CONDITIONS TO AVOID): Stable
 INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidizing and reducing agents.
 HAZARDOUS DECOMPOSITION PRODUCTS: N.AP.
 HAZARDOUS POLYMERIZATION (CONDITIONS TO AVOID): Will not occur

 6. HEALTH HAZARD DATA

PRIMARY ROUTES OF ENTRY: INHALATION____ SKIN_X__ INGESTION____

WARNING! MAY CAUSE EYE AND SKIN IRRITATION. MAY BE HARMFUL IF SWALLOWED.

SIGNS & SYMPTOMS OF EXPOSURE: (ACUTE & CHRONIC)

EYES: Liquid and vapors may cause irritation.
 SKIN: Prolonged contact may cause severe irritation.
 INGESTION: May cause abdominal pain and discomfort.

6. HEALTH HAZARD DATA (cont'd)

INHALATION: Not likely route of exposure.
 IRRITANCY OF PRODUCT: Slight irritant.
 SENSITIZATION TO PRODUCT: N.AV.
 CARCINOGENICITY, REPRODUCTIVE TOXICITY, TERATOGENICITY, MUTAGENICITY: N.AV.
 TOXICOLOGICALLY SYNERGISTIC PRODUCTS: N.AV.

EMERGENCY AND FIRST AID PROCEDURES:

EYES: Remove contact lenses, if worn. Flush with water for at least 15 min. Call a physician.
 SKIN: Remove any contaminated clothing, wash area with water or soap and water for at least 15 minutes, get medical attention.
 INHALATION: Remove to fresh air. If breathing is difficult get medical help.
 INGESTION: If conscious, give large amounts of water, induce vomiting, get medical help.

7. SPILL AND LEAK PROCEDURES

LARGE SPILLS: Contain and transfer to container for use or disposal.
 SMALL SPILLS: Absorb onto rags and clean rags in cleaning unit.
 WASTE DISPOSAL METHOD: May be considered a hazardous waste, dispose of according to all applicable regulations. Incineration in permitted facilities or disposal in permitted landfills is preferred disposal methods.
 HANDLING PROCEDURES & EQUIPMENT: Avoid direct contact with product.
 STORAGE REQUIREMENTS: None

8. SPECIAL PROTECTION, PREVENTATIVE MEASURES/IN CASE OF LARGE SPILL OR FIRE

ENGINEERING CONTROLS/VENTILATION: Local exhaust system.

RESPIRATOR: THE FOLLOWING RESPIRATORS ARE RECOMMENDED & RANKED IN ORDER FROM MIN. TO MAX. PROTECTION:

CHEMICAL CARTRIDGE RESPIRATOR WITH AN ORGANIC VAPOR CARTRIDGE WITH A FULL FACE PIECE.
 GAS MASK WITH ORGANIC VAPOR CANISTER WITH A FULL FACE PIECE.
 TYPE 'C' SUPPLIED-AIR RESPIRATOR WITH FULL FACE PIECE.
 SELF-CONTAINED BREATHING APPARATUS WITH A FULL FACE PIECE OPERATED IN PRESSURE-DEMAND

PERSONAL PROTECTIVE EQUIPMENT: Wear goggles when handling product.

9. TRANSPORTATION DATA

DOT HAZARD CLASSIFICATION 49 CFR172.101: None, not regulated
 DOT LABEL: None
 U.N./IATA: Not regulated

10. STATE RIGHT TO KNOW INFORMATION

WATER C.A.S. # 7732-18-5, FATTY ACID SALTS – C.A.S. #(NONE), DIOCTYL SULFOSCCLINATE C.A.S. #577-11-7,
 ISOPROPYL ALCOHOL C.A.S. #67-63-0, HEXYLENE GLYCOL C.A.S. #107-41-5

ABBREVIATIONS:

OSHA = Occupational Safety & Health Administration	C.A.S. = Chemical Abstract Service Number
TWA = Time Weighted Average for 8 Hours	LD 50 = Lethal Dose for 50% Test Animals
Mg/M ³ = Milligrams per Cubic Meter of Air	PEL = Permissible Exposure Level
NFPA = National Fire Protection Agency	STEL = Short Term Exposure Level (15 min)
(C) = Ceiling, Limit for Exposure	ppm = part(s) per million
DOT = Department of Transportation	SKN = Skin Effects
MG/KG = Milligrams per Kilogram (1,000 grams)	IATA = International Air Transport Association
WHMIS = Workplace Hazardous Materials Information System - Canada	N.AV. = Not Available
ACGIH = American Conference of Government Industrial Hygienists	N.AP. = Not Applicable
R.Q. = Amount of spill that must be reported to EPA	U.N. = United Nations
SARA Title III, Sec. 313 = Superfund Amendments and Reauthorization Act	

WE CANNOT ANTICIPATE ALL CONDITIONS UNDER WHICH THIS INFORMATION AND OUR PRODUCTS, OR THE PRODUCTS OF OTHER MANUFACTURERS IN COMBINATION WITH OUR PRODUCTS, MAY BE USED. WE ACCEPT NO RESPONSIBILITY FOR RESULTS OBTAINED BY THE APPLICATION OF THIS INFORMATION OR THE SAFETY AND SUITABILITY OF OUR PRODUCTS, EITHER ALONE OR IN COMBINATION WITH OTHER PRODUCTS. WE SELL THE PRODUCTS WITHOUT WARRANTY, AND BUYERS AND USERS ASSUME ALL RESPONSIBILITY AND LIABILITY FOR LOSS OR DAMAGE ARISING FROM THE HANDLING AND USE OF OUR PRODUCTS, WHETHER ALONE OR IN COMBINATION WITH OTHER PRODUCTS.