

MATERIAL SAFETY DATA SHEET

FABRITEC INTERNATIONAL
 1157 INDUSTRIAL ROAD
 COLD SPRING, KY 41076
 EMERGENCY CONTACT: HAROLD E. MAINS (859) 781-8200
 CHEMTREC ASSISTANCE: (800) 262-8200 (U.S.A. & CANADA)

MSDS NO: 6947
 DATE: April 2010
 PAGE: 1 OF 2

1. PRODUCT NAME & HAZARD SUMMARY

6947 Fabric Finish

PRIMARY USE: SPECIAL BLEND CONDITIONER FOR COTTON BLENDS & CASUAL WEAR

NFPA HAZARD	RATING	SARA TITLE III, SECTION 313	CANADA (WHMIS)
HEALTH	1 SLIGHT	APPLICABLE ()	D2: CAUSING OTHER TOXIC EFFECTS
FIRE	2 MODERATE	NOT APPLICABLE (X)	B: FLAMMABLE, COMBUSTIBLE
REACTIVITY	0 MINIMAL		

2. HAZARDOUS COMPONENTS

	%	OSHA (PPM)	ACGIH (PPM)	LD 50 (MG/KG)
ISOPROPYL ALCOHOL	<10	PEL 400	TWA 400	STEL 500

C.A.S. #67-63-0

INGREDIENTS NOT IDENTIFIED ARE NON-HAZARDOUS.

3. PHYSICAL & CHEMICAL DATA

APPEARANCE: CLEAR WHITE TO YELLOW LIQUID	EVAPORATION RATE (ETHER = 1): EQUAL TO WATER
ODOR: PERFUMED	VAPOR DENSITY (AIR = 1): N. AP.
BOILING PT: 212 °F (100°C)	VAPOR PRESSURE (MM): N.AP.
FREEZING PT: 32°F (0°C)	SOLUBILITY IN WATER: COMPLETE
pH: 4.5 -5.5	SPECIFIC GRAVITY (WATER = 1): 1.00
% VOLATILE: 75-80%	CO-EFFICIENT OF WATER/OIL DIST: N.AV.
ODOR THRESHOLD (PPM): N.AV.	

4. FIRE & EXPLOSION HAZARDS

FLASH POINT: 104°F (41°C)
 FLAMMABLE LIMITS IN AIR, % BY VOLUME: 12.70 (ISOPROPYL ALCOHOL)
 FIRE FIGHTING MEDIA (1990 EMERGENCY RESPONSE GUIDEBOOK, DOT P 5800.5): Dry chemical, CO₂, water or foam spray.
 SPECIAL FIRE-FIGHTING PROCEDURES: Wear self-contained breathing apparatus.
 UNUSUAL FIRE & EXPLOSION: None
 HAZARDOUS COMBUSTION PRODUCTS: Oxides of Carbon
 CONDITIONS OF FLAMMABILITY: N.AP.
 AUTO IGNITION TEMP (°C): N.AP.
 EXPLOSION DATA, SENSITIVITY TO MECHANICAL IMPACT: N.AP.
 SENSITIVITY TO STATIC DISCHARGE: N.AP.

5. REACTIVITY HAZARD DATA

STABILITY (CONDITIONS TO AVOID): Stable
 INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidizers
 HAZARDOUS DECOMPOSITION PRODUCTS: Thermal decomposition may release Oxides of Carbon
 HAZARDOUS POLYMERIZATION (CONDITIONS TO AVOID): Will not occur

6. HEALTH HAZARD DATA

PRIMARY ROUTES OF ENTRY: INHALATION X SKIN X INGESTION

WARNING! MAY CAUSE EYE, SKIN AND RESPIRATORY IRRITATION. MAY BE HARMFUL IF SWALLOWED.

SIGNS & SYMPTOMS OF EXPOSURE: (ACUTE & CHRONIC)

EYES: Liquid and vapors may cause irritation.
 SKIN: Prolonged contact may cause defatting of the skin which can lead to irritation and dermatitis.
 INGESTION: of a large dose may cause abdominal pain, nausea and vomiting.
 INHALATION: Low hazard unless heated or misted.
 IRRITANCY OF PRODUCT: Minimal
 SENSITIZATION TO PRODUCT: N.AV.
 CARCINOGENICITY, REPRODUCTIVE TOXICITY, TERATOGENICITY, MUTAGENICITY: N.AV.
 TOXICOLOGICALLY SYNERGISTIC PRODUCTS: N.AV.

6. HEALTH HAZARD DATA (cont'd)

EMERGENCY & FIRST AID PROCEDURES:

EYES: Remove contact lenses, if worn. Flush with water for at least 15 minutes. Call a physician.

SKIN: Remove contaminated clothing; wash affected area with soap and water. Get medical help if symptoms occur.

INHALATION: Remove to fresh air.

INGESTION: Treat symptomatically and supportively. Get medical attention immediately. If vomiting occurs, keep head below knees to prevent aspiration into lungs.

7. SPILL & LEAK PROCEDURES

Remove sources of ignition.

LARGE SPILLS: Contain and transfer to drums for use or disposal.

SMALL SPILLS: Absorb onto rags. Clean rags in cleaning unit.

WASTE DISPOSAL METHOD: May be considered a hazardous waste, dispose of according to all applicable regulations. Incineration in permitted facilities or disposal in permitted land fills are preferred disposal methods.

HANDLING PROCEDURES & EQUIPMENT: Avoid direct contact.

STORAGE REQUIREMENTS: Keep away from oxidizers.

8. SPECIAL PROTECTION, PREVENTATIVE MEASURES/IN CASE OF LARGE SPILL OR FIRE

ENGINEERING CONTROLS/VENTILATION: Normal room ventilation

RESPIRATOR: THE FOLLOWING RESPIRATORS ARE RECOMMENDED & RANKED IN ORDER FROM MIN. TO MAX. PROTECTION:

CHEMICAL CARTRIDGE RESPIRATOR WITH AN ORGANIC VAPOR CARTRIDGE WITH A FULL FACE PIECE

GAS MASK WITH ORGANIC VAPOR CANISTER WITH A FULL FACE PIECE

TYPE "C" SUPPLIED-AIR RESPIRATOR WITH FULL FACE PIECE

SELF-CONTAINED BREATHING APPARATUS WITH A FULL FACE PIECE OPERATED IN PRESSURE-DEMAND

PERSONAL PROTECTIVE EQUIPMENT: Wear goggles when handling product.

9. TRANSPORTATION DATA

DOT HAZARD CLASSIFICATION 49 CFR172.101: Combustible liquid not regulated for ground shipments

DOT LABEL: None

U.N./I.A.T.A.: Class 3, PKG. Group:III

10. STATE RIGHT TO KNOW INFORMATION

WATER-C.A.S. #7732-18-5, VINYL ALCOHOL POLYMERS-C.A.S. #90002-89-5,
VINYL ACETATE/VINYLPYRROLIDONE COPOLYMER-C.A.S. #67892-37-9, SILICONE SURFACTANT-C.A.S. # (None),
ISOPROPYL ALCOHOL-C.A.S. #67-63-0

ABBREVIATIONS:

OSHA: Occupational Safety & Health Administration

TWA: Time Weighted Average for 8 Hours

Mg/M³= Milligrams per Cubic Meter of Air

NFPA = National Fire Protection Agency

(C): Ceiling, Limit for Exposure

DOT = Department of Transportation

MG/KG = Milligrams per Kilogram (1,000 grams)

WHMIS = Workplace Hazardous Materials Information System - Canada

ACGIH = American Conference of Government Industrial Hygienists

R.Q. = Amount of spill that must be reported to EPA

SARA Title III, SEC 313 = Superfund Amendments and Reauthorization Act

C.A.S. = Chemical Abstract Service Number

LD 50 = Lethal Dose for 50% Test Animals

PEL = Permissible Exposure Level

STEL = Short Term Exposure Level (15 min)

ppm = part(s) per million

SKN = Skin Effects

IATA = International Air Transport Association

N.A.V. = Not Available

N.AP. = Not Applicable

U.N. = United Nations

WE CANNOT ANTICIPATE ALL CONDITIONS UNDER WHICH THIS INFORMATION AND OUR PRODUCTS, OR THE PRODUCTS OF OTHER MANUFACTURERS IN COMBINATION WITH OUR PRODUCTS, MAY BE USED. WE ACCEPT NO RESPONSIBILITY FOR RESULTS OBTAINED BY THE APPLICATION OF THIS INFORMATION OR THE SAFETY AND SUITABILITY OF OUR PRODUCTS, EITHER ALONE OR IN COMBINATION WITH OTHER PRODUCTS. WE SELL THE PRODUCTS WITHOUT WARRANTY, AND BUYERS AND USERS ASSUME ALL RESPONSIBILITY AND LIABILITY FOR LOSS OR DAMAGE ARISING FROM THE HANDLING AND USE OF OUR PRODUCTS, WHETHER ALONE OR IN COMBINATION WITH OTHER PRODUCTS.